



Fastmark PT-1 Series

Portable Yet Rugged And Reliable

PT-1 – Perfect for mobile label, tag and wristband printing

The PT-1 is a lightweight compact printer ideally suited for a wide variety of mobile applications from receipts to barcode labels. Couple the Bluetooth version with a Bluetooth scanner for the perfect patient bedside specimen label solution. Our PAL programming language makes the PT-1 an intelligent printer allowing customization of output.

Standard Features

- PAL Plus and Zebra emulations
- RS-232, USB, IrDA, Bluetooth and WIFI interfaces
- 203 dpi printhead resolution
- Print speeds up to 3 ips
- Real time clock
- Clamshell design for easy media loading
- Supports both gap and black bar media
- Smart battery management
- Smart power supply monitoring
- Belt clip and shoulder strap options
- Direct thermal printing on all popular media material



Fastmark PT-1 Series – Portable labeling and wristband printing

Applications include:

- Emergency mobile wristband printing
- Bedside specimen label printing
- Pharmacy medication labels
- Manufacturing product labels
- Shipping/receiving labels
- Inventory control labels



PRINTER SPECIFICATIONS INCLUDE:

Printer Model	Fastmark PT-1
Resolution	203 dpi
Command Set	PAL Plus, ZPL
Printing Method	Direct Thermal
Print Speed	Up to 3 ips
Max Print Width	2.8 inches
Max Print Length	40 inches
Media width	1.0" – 3.0"
Media Core diameter	0.5"
Label Roll Capacity	2.2" OD
Media Types	Wristbands, continuous, die-cut, tag, black mark
Sensors	Gap, black mark reflective, head open, paper out
Enclosure	Clamshell design with belt clip or shoulder strap
Processor	32-bit RISC CPU
Memory	4MB Flash 8MB DRAM
Real time clock	Standard
Interfaces	USB, RS-232, IrDA or USB, RS-232, IrDA, Bluetooth Optional WiFi

Linear Bar Codes	Standard 2 of 5, Industrial 2 of 5, Code 39, Code 93, Code 128 subsets, A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, Logmars, Code 11, GSI Data Bar
2D Bar Codes	PDF-417, Maxicode, Data Matrix, QR Code, Aztec, Composite Codes
Windows Compatibility	Operating systems WIN 7/8
Dimensions	4.2" W x 2.8" H x 6" D 1.5 lbs. including battery and media
Battery	Rechargeable 7.4V Lithium-ion, 2200mAh, Operating 8 hours, standby 14 hours
Standard items	Belt clip, 1 Battery, AC adapter, cleaning pen, sample receipt roll, Quick Guide
Options	Shoulder strap, Environment case, Single battery charger, Spare battery, 4 bay battery charger, Vehicle power adapter
Power	Input: AC 100-240V, 50 – 60Hz Output: 9 VDC, 1.56 A
Environment Conditions	Operation: 14 – 122 F, 0 – 90% non-condensing Storage: -4 – 140 F, 10 – 90% non-condensing
Warranty	Two years Printer, 1 year printhead
Agency Approval	FCC, cTUVus

All products are trademarks of their respective owners. Specifications are subject to change without notice. Some models and features may not be currently available. Some options and features are not available on all models.



Part No. 140228 rev. B
Specifications are subject to change without notice.

Corporate Headquarters
803 Camarillo Springs Road, Suite D,
Camarillo, CA 93012
(805) 388-5799 PH
(805) 484-5282 FX

www.amtdatasouth.com

Charlotte Operation
5033 Sirona Drive, Suite 800
Charlotte, NC 28273
(704) 523-8500 PH
(704) 525-6104 FX